2-Port Compact PS/2 KVM Switch w/Audio and Cable

MODEL NUMBER: **B004-VPA2-K-R**

Highlights

- Fast, easy switching via keyboard hot keys or push buttons
- Allows sharing of audio components between systems; listen to music from one computer while accessing another
- Compact design saves desk space
- No software or AC adapter required
- (x2) 6ft PS/2 KVM Cable kits and (x2) 6ft 3.5mm Audio Cable Kits included
- Compatible with all major operating systems

System Requirements

- Console: VGA, SVGA or Multisync Monitor, PS/2 Keyboard and PS/2 Mouse
- Computers: VGA, SVGA or Multisync Monitor Port, PS/2 Keyboard Port and PS/2 Mouse Port
- Audio (Optional): Speakers with standard 3.5mm Connectors and a computer with 3.5mm ports
- Compatible with all major operating systems

Package Includes

- Compact 2-port PS/2 KVM Switch with Audio
- (2) 6ft PS/2 KVM Cable Kits and (2) 6ft 3.5mm Audio Cable Kits

Description

The B004-VPA2-K-R is a 2-port Compact PS/2 KVM Switch with optional audio and microphone switching function. It allows you to access, control, boot and reboot two PS/2-enabled computers from a single console (keyboard, monitor and mouse). The independent audio/mic switching function allows an uninterrupted audio experience - you can continue listening to audio even when you switch to the other computer. Compatible with all major operating systems.

Features

- Fast, easy switching via keyboard hot keys or push buttons
- Plug-and-play setup - no software required
- Hot-swap capability allows easy addition or removal of computers without powering down the switch or other computers
- Speaker and microphone connections allow sharing of audio components between systems (standard 3.5 mm audio connections)
- Independent audio switching allows you to listen to audio from one computer while switching to the other computer
- Supports video resolutions up to 2048 x 1536 (standard 15-pin VGA connectors)
- Supports Microsoft® IntelliMouse® and the scrolling wheel on most mice
- Compact design saves desk space
- Does not require an AC adapter
- Compatible with all major operating systems
- Includes two, 6ft Cable Kits

- Owner's Manual with Warranty Information

Specifications

OVERVIEW	
UPC Code	037332140050
Users	1
Console	No
Max CPU	2
Technology	PS/2; VGA/SVGA; Stereo Audio
PHYSICAL	
Shipping Dimensions (hwd / in.)	3.000 x 7.400 x 7.600
Shipping Dimensions (hwd / cm)	7.62 x 18.80 x 19.30
Shipping Weight (lbs.)	1.9000
Shipping Weight (kg)	0.86
Color	Black
LCD Monitor (in.)	Not Applicable
LCD Monitor (cm)	Not Applicable
ENVIRONMENTAL	
BTUs	17.065
COMMUNICATIONS	
Port Control	Push Buttons, Hotkeys
IP Remote Access	No
CONNECTIONS	
Ports	2
PC/Server Connections	PS/2; VGA
Included KVM Cable (Equipment Side) - Connector 1	HD15 (Male)
Included KVM Cable (Equipment Side) - Connector 2	(x2) MiniDIN6 (Male)
Included KVM Cable (Equipment Side) - Connector 3	(x2) 3.5mm (Male)

Local Console Ports - Port 3	(x2) 3.5mm (Female)
CERTIFICATIONS	
Certifications	FCC, CE, RoHS Compliant
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty