


# QT-Brightek Lamp Series 5mm Round Deep Red LED

Part No.: QBL7SA60D

Product: QBL7SA60D	Date: January 22, 2018	Page 1 of 7
	Version# 1.0	








Table of Contents:	
Introduction	3
Electrical / Optical Characteristic (Ta=25 °C)	4
Absolute Maximum Rating	
Characteristic Curves	5
Ordering Information	6
Revision History	7
Disclaimer	

Product: QBL7SA60D	Date: January 22, 2018	Page 2 of 7
	Version# 1.0	



# Introduction

### **Feature:**

- Color diffused lens
- Package in bulk pack
- 5mm round lamp
- AlGaAs technology
- Viewing angle: 60° typ.

### **Description:**

These bright 3mm round type lamps are suitable for all indicator applications such as electronic signs and electronics board indicator

## **Application:**

- General purpose indicator application
- Electronic signs and electronics board


# **Certification & Compliance:**


- TS16949
- ISO9001
- RoHS Compliant




## **Dimension:**









Units: mm / tolerance = +/-0.25mm unless otherwise specified

Product: QBL7SA60D	Date: January 22, 2018	Page 3 of 7
	Version# 1.0	



# Electrical / Optical Characteristic (Ta=25°C)

Product	Color	I <sub>F</sub> (mA)	V <sub>F</sub> (V)		λ <sub>D</sub> (nm)	l <sub>∨</sub> (m	cd)
			Тур.	Max.	Тур.	Min.	Тур.
QBL7SA60D	Deep Red	20	1.8	2.4	640	20	45

# **Absolute Maximum Rating**


Material	P <sub>d</sub> (mW)	I <sub>F</sub> (mA)	I <sub>FP</sub> (mA)*	V <sub>R</sub> (V)	T <sub>OP</sub> (°C)	T <sub>ST</sub> (°C)
AlGaAs	60	25	100	5	-40 ~ +85	-40 ~ +100


<sup>\*1/10</sup> Duty Cycle, 0.1ms Pulse Width


Product: QBL7SA60D	Date: January 22, 2018	Page 4 of 7
	Version# 1.0	





# **Characteristic Curves**














Product: QBL7SA60D	Date: January 22, 2018	Page 5 of 7
	Version# 1.0	



# QBL7SA60D

3mm Round Lamp

**Ordering Information** 

Part #	Orderable Part #	Spec Range	Quantity per bag
QBL7SA60D	QBL7SA60D	Iv=45mcd typ. @ 20mA, $\lambda_D$ =640nm typ.	500pcs

Product: QBL7SA60D	Date: January 22, 2018	Page 6 of 7
	Version# 1.0	



**Revision History** 

Description:	Revision #	Revision Date
New Release of QBL7SA60D	V1.0	02/14/2018

### **Disclaimer**

QT-BRIGHTEK reserves the right to make changes without further notice to any products herein to improve reliability, function or design. QT-BRIGHTEK does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

# **Life Support Policy**

QT-BRIGHTEK's products are not authorized for use as critical components in life support devices or systems without the express written approval of QT-BRIGHTEK. As used herein:

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- 2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Product: QBL7SA60D	Date: January 22, 2018	Page 7 of 7
	Version# 1.0	