



Part Number: 39110

Hook-Up/Lead Wire PPO, 600V, 105°C AWM Style 11032, (1) 10 AWG (105x30) TC, PPO, 600V, 105°C

Request Sample

Product Description

One 10 AWG stranded (105x30) tinned copper conductor, polyphenylene oxide (PPO) insulation.

Technical Specifications

Product Overview

Suitable Applications:	Electrical panel builders, Electrical/electronic manufacturers, Appliance manufacturers, Furniture, Computer manufacturers, Automotive companies and their sub-suppliers
------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
10	105x30	TC - Tinned Copper	1
Conductor Count:		1	
Condu	uctor Size:		10 AWG

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
PPO - Polyphenylene Oxide	0.134 in	0.012 in

Outer Jacket Material

Material No Jacket

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
1 Ohm/1000ft

Shielding: Unshielded

Current

Element	Max. Recommended Current [A]
Single conductor in free air @ 30C ambient	67.0 A

Voltage

UL Voltage Rating

Temperature Range

UL Temp Rating:	105°C
Operating Temp Range:	-40°C To +105°C Dry

Mechanical Characteristics

Bulk Cable Weight: 36.5 lbs/1000ft

Standards

UL AWM Style: AWM 11028

Military Specification: N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2011-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
UL voltage rating:	600 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No.

Part Number

Variants

Item #	Color	Footnote
39110 010100	Black	С
39110 0101000	Black	С
39110 0105000	Black	С
39110 013100	Blue, Dark	С
39110 0135000	Blue, Dark	CZ
39110 001100	Brown	
39110 0011000	Brown	С
39110 0015000	Brown	CZ
39110 008100	Gray	С
39110 0085000	Gray	CZ
39110 0051000	Green, Dark	С
39110 0055000	Green, Dark	CZ
39110 189100	Green, Yellow Stripe	С
39110 1895000	Green, Yellow Stripe	CZ
39110 003100	Orange	С
39110 0035000	Orange	CZ
39110 002100	Red	С
39110 0021000	Red	С
39110 0025000	Red	С
39110 007100	Violet	С
39110 0075000	Violet	CZ
39110 009100	White	С
39110 0095000	White	CZ
39110 004100	Yellow	
39110 0045000	Yellow	CZ

Footnote:	C - CRATE REEL PUT-UP.	
Footnote:	Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.	

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product

Disclosure is not to be considered a warranty or quality specification. Regulator regulations based on their individual usage of the product.	ry information is for guidance purposes	s only. Product users are responsible fo	r determining the applicability of legi	slation and