



ELECTRICAL CHARACTERISTICS

- Impedance: 50 Ohm
- Working frequency: 1GHz max
- Dielectric with standing voltage: 600V
- Insulation resistance 5000: 14 Ohm
- Contact resistance < 5 mOhm
- Insertion lost: < 0.2 dB

MECHANICAL CHARACTERISTICS

- Mating force per set of contact 0.4 N to 9 N
- Mating endurance 500
- Temperature -55° to +125 °C

TOOLING

- Coaxial contact extraction tool 8630-07A

DM537405005NCLF	STRAIGHT MALE COAXIAL CONTACT	3.15	4	5.09	5.95	RG 58 C/U
PART NUMBER	DESIGNATION	ϕA $^{+0.10}_0$	ϕB ± 0.05	ϕC $^{+0.10}_0$	ϕD ± 0.10	Cable ref.

NOTE:RoHS INFORMATIONS

- The "LF" product meets European union Directives and other country regulations as described in GS-22-008.
- The product is not intended to be exposed to a manufacturing solder process.
- Packaging spec: see GS-14-920.

rev	ecn no	dr	date
A	LS05-0086	MPE	2005/10/12
B	LS05-0107	MPE	2005/12/20
C	LS07-0001	MPE	2007/01/09
D	F10-0086	LSA	2010/08/20
-	-	-	-
-	-	-	-
-	-	-	-

www.fciconnect.com		surface ISO 1302 <input checked="" type="checkbox"/>	tolerance std ISO 406 ISO 1101	projection 	mm
TOLERANCES UNLESS OTHERWISE SPECIFIED					
Dr	PESSON	2005/10/12	ANGULAR	0.X	± 0.1
Eng	PESSON	2005/10/12	LINEAR	0.XX	± 0.1
Chr	LEGARE	2005/10/12	0.XX ± 2	0.XXX	± 0.1
Appr	LEGARE	2005/10/12	Product family		D-SUB
				size	A3
				Scale	5
				ECN	F10-0086
				Spec ref	-
title STRAIGHT MALE COAXIAL CONTACT			dwg no C01-8639-2147		Rev. D
catalog no			CUSTOMER		sheet 1 of 1