
KEMET Part Number: T502B106K016AG6210



T502, Tantalum, MnO2 Tantalum, High Temperature, 10 uF, 10%, 16 VDC, SMD, MnO2, Un-Encapsulated, High Temperature, 230C, N/A, 2.8 Ohms, 3528, Height Max = 2.1mm



Dimensions		
Footprint	3528	
L	3.5mm +/-0.2mm	
W	2.8mm +/-0.2mm	
Н	1.9mm +/-0.2mm	
Т	0.13mm REF	
S	0.8mm +0.1/-0.3mm	
F	2.2mm +/-0.1mm	
A	1.9mm MIN	
В	0.4mm +/-0.15mm	
Р	0.5mm REF	
R	1mm REF	
Х	0.1mm +/-0.1mm	

Packaging Specifications		
Packaging:	T&R, 178mm	
Packaging Quantity:	2000	

General Information		
Supplier:	KEMET	
Series:	T502	
Dielectric:	MnO2 Tantalum	
Style:	SMD Chip	
Description:	SMD, MnO2, Un-Encapsulated, High Temperature, 230C	
Features:	230C	
RoHS:	Yes	
Termination:	Gold	
Notes:	In Polarity Stripe, At KEMET'S Option, Type May Be Indicated: No Symbol = Standard (Or Low Leakage) MnO2 Tantalum Chip, O = LowESR T494, R = Low ESR T495, F = Fused T496, HT = 150C Rated T498 (or B45196P, B45198P), H = 175C rated T499, M = Multiple Anode	
Shelf Life:	156 Weeks	
MSL:	1	

Specifications		
Capacitance:	10 uF	
Capacitance Tolerance:	10%	
Voltage DC:	16 VDC (85C), 13.1 VDC (125C), 5.3 VDC (230C)	
Temperature Range:	-55/+230C	
Rated Temperature:	85C	
Dissipation Factor:	6.00% 120Hz 25C	
Failure Rate:	N/A	
Resistance:	2.8 Ohms (100kHz 25C)	
Ripple Current:	174 mA (100kHz 45C)	
Leakage Current:	1.6 uA (5min 25C)	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

